



SCRUBBER DRIERS - WALK BEHIND

CT40

MAX PRODUCTIVITY

2475 m²/h

BATTERIES
RUNNING TIME

2,5 h

WATER TANK
RUNNING TIME

45 min
working session



INNOVATIONS



DBL™
DOUBLE
BATTERY
LIFE



SLS™
SELF
LEVELING
SYSTEM

SPECS



INTUITIVE CONTROL PANEL



ANTI-FOAM SYSTEM WITH
SPECIAL ELECTROMECHANICAL
SUCTION MOTOR PROTECTION

MOST FREQUENTLY USED



RETAIL



HOSPITALITY



BUILDING SERVICE CONTRACTORS



MUNICIPALITIES

TECHNICAL DATA

	CT40 BT50
Code	
PERFORMANCE	
Max theoretical productivity	2250 m ² /h
Cleaning path	500 mm
Water tank capacity (solution recovery)	40/50 l
Max running time	140 min
Voltage	24(2x12)-105 GEL V-Ah
Installed power	1250 W
Brush pressure	18 kg
Squeegee width	815 mm
Max speed	4,5 km/h
Weight	73 kg
Dimension (LxWxH)	1230 x 516 x 960 mm

CONSUMABLES (Codes available on price list)

BRUSHES



SPPV01498 | POLYPROPYLENE (PP) BRUSH

PADS



L-17260 | 20' POLISH PAD - WHITE
 L-17261 | 20' BUFF PAD - RED
 L-17262 | 20' SCRUB PAD - BLUE
 L-1243339 | 20' BUFF PAD - RED (BOX OF 5)
 L-1243352 | 20' POLISH PAD - WHITE (BOX OF 5)

SQUEEGEE BLADES



MPVR08039 | LATEX FRONT BLADE
 MPVR08035 | LATEX REAR BLADE

IPC Australia
 Unit 11, 4 Southridge Street
 Eastern Creek NSW 2766

T: 1800 226 843 (FREE CALL)
 T: +61 2 9839 9700

E: contactanz@ipcworldwide.com
 W: www.ipcworldwide.com

IPC New Zealand
 Unit 5, 103 Cryers Road
 East Tamaki
 Auckland 2013

T: +64 9 253 9013
 F: +64 9 253 9015